

**FAIRFAX LED SERIES**

Fairfax LED Wall Sconce features a Luminous Diffuser in Acrylic, Decorative Square Bar Design with Ball Accent, ADA Compliant

|             |  |      |
|-------------|--|------|
| Catalog #   |  | Type |
| Project     |  |      |
| Comments    |  | Date |
| Prepared By |  |      |

**EVERGREEN LIGHTING**

**SPECIFICATION FEATURES**

**Material**

Aluminum Square Bar construction slotted and milled for high quality appearance, standard powdercoat finish, P95 white frosted acrylic half cylinder lens, .125 thick, with open top and bottom.

**Installation**

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

**Optics**

Evergreen Lighting Website for complete photometrics.

**LED**

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage. The LED arrays will be centered within the Lens area and mounted on a decorative white aluminum reflective plate.

**Driver**

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 3 or 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67










15"H X 7"W X 4"D  
 19"H X 9"W X 5 1/2"D  
 24"H X 10"W X 5 1/2"D

**Fairfax Series**

DELIVERED LUMENS PER WATT  
 2700K = 80  
 3000K = 90  
 3500K = 100  
 4100K = 110  
 5000K = 120

**ORDERING INFORMATION**

Sample Number: FFX-W-24W-AB-WF

|   |   |   |   |  |   |  |
|---|---|---|---|--|---|--|
|  |  |  |      |   |   |   |
| <b>Series</b><br>FFX  | <b>Style</b><br>Wall  | <b>Size</b><br>15"<br>19"<br>24"  | <b>LED</b><br>15"<br>12W<br>18W<br>24W<br>19"<br>12W<br>24W<br>30W<br>24"<br>20W<br>40W | <b>Finish</b><br>Architectural Bronze (AB)<br>Textured Bronze (TBR)<br>Matte Black (MBK)<br>Semi Gloss Black (GBK)<br>Textured Black (TBK)<br>Textured Rust (TR)<br>Matte White (MW)<br>Textured White (TW)<br>Gloss White (GW)<br>Metallic Grey (MG)<br>Brushed Aluminum (BA) adder<br>Metallic Nickel (MN)<br>Textured Verde Patina (TVP)<br>Satin Brass (SB)<br>Copper Vein (CV)<br>Gold Vein (GV)<br>Silver Vein (SV)<br>Chrome (CH) | <b>Lens</b><br>White Frosted (WF)<br>White Alabaster (WA)<br>Honey Onyx (HO)<br>Natural Horn (NH)<br>Beige Alabaster (BA)<br>Honey Swirl (HS) | <b>Options</b><br>EMR, 650 Lumen<br>EMR, 900 Lumen<br>Dimming Drivers<br>Design Modifications<br>Larger size in ADA<br>Wet Location<br>(Top and Bottom Lens) |

Labels  
 ETL for US and  
 Canada for damp  
 location