

BALBOA LED SERIES

Balboa LED Wall Sconce features a Rugged Solid Aluminum Round Bar Trim with One Horizontal Bar and One Round Circle Design with a Luminous Quartersphere Diffuser in Acrylic, ADA Compliant

Catalog #		Type
Project		
Comments		Date
Prepared By		

EVERGREEN LIGHTING

SPECIFICATION FEATURES

Material

Aluminum Round Bar construction with a Rugged Quarter-sphere Shaped Trim with One Horizontal Bar and One Round Circle Design, standard powdercoat finish, white smooth acrylic quartersphere shaped lens, .125 thick, with open top.

Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Optics

Contact Evergreen Lighting for complete photometrics.

LED


Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage. The LED arrays will be centered within the Lens area and mounted on a white aluminum reflective backplate.

Driver

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67

Driver Options:
0-10V Dimming
Phase Dimming
Triac Dimming



6"H X 12"W X 4"D
8"H X 16"W X 4"D

Balboa Series

Labels
ETL for US and
Canada for damp
location

ORDERING INFORMATION

Sample Number: BB-W-16-24W-TBK-A

Series BB	Style Wall	Size 12" 16"	LED 12" 6W 12W 16" 12W 24W	Finish Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Textured Gold (TG) Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV) Polished Brass (PB) Adder Chrome (CH)	Lens White Acrylic (A) White Frosted (WF) White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS)	Options Remote EMR, 700 Lumen Remote EMR, 900 Lumen Dimming Drivers Design Modifications Larger size in ADA
	LED to CFL Lamp 6W = (1) F13DBX 12W = (2) F13DBX (1)F26DBX 24W = (2)F26DBX					