Eclipse LED Pendant

Eclipse LED Pendant Series features a low profile bowl and is available in two diameters.

Catalog #	Туре
Project	LED
Comments	Pendant
Prepared By	Date

EVERGREEN LIGHTING

SPECIFICATION FEATURES

Material

Aluminum solid flat bar construction with an aluminum spun canopy for standard powdercoat finish or polished brass plated finish with P95 frosted white acrylic bowl. Single stem design with a drop disc connecting 3 aircraft cables, with a 45 degree swivel mount.

Maximum overall hang height for one piece stem assembly is 5' (OA). Lengths from 5' to 25' must have a 5/8" deco connector that will be provided. Any lengths over 25'contact Factory.

Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Optics

Contact Evergreen Lighting for complete photometrics.

LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage.

The LED arrays will be centered within the Lens area and mounted on a decorative white aluminum reflective plate.

Driver

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 3 or 5 year warranty
- 120/277 multi voltage
- IP66, IP67

90W



29" diameter X11"H on bowl X 35" overall height

35" diameter X 15"H on bowl X 38" overall height

DELIVERED LUMENS PER WATT

2700K = 80


3000K = 90


3500K = 100

4100K = 110

5000K = 120

ORDERING INFORMATION





Evergreen Lighting www.evergreenlighting.com

Finish

Chrome (CH)

Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Brushed Aluminum (BA) adder Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV)

Standard Lens

White Frosted (WF)

Optional Lens White Alabaster (WA) Honey Onyx (HO)

Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS)

Options

LED EMR - Up to 24W (lota ILB-3020) Dimming Drivers Stem Rod Length Swivel Canopy 29" Dust Cover 35" Dust Cover Multiple Rod Design

Labels

ETL for US and Canada for indoor and damp location.