

EXCALIBUR LED CEILING SERIES

Excalibur LED Flush Square Pointed Ceiling Fixture features a Craftsman Style Cage Design with a Slotted Trim, Acrylic Panels, and displays a clean contemporary look.

Catalog #		Type
Project		
Comments		Date
Prepared By		

EVERGREEN LIGHTING

SPECIFICATION FEATURES

Material

Paintlok Non-Rustable Steel construction spot welded for high quality appearance, punched slotted design, standard powdercoat finish, P95 white smooth acrylic flat panels, .125 thick.

LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage. The LED arrays will be centered within the Lens area and mounted on a white aluminum reflective backplate.

Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Driver

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67

Optics

Contact Evergreen Lighting for complete photometrics.



10" Wide X 5" Deep
14" Wide X 5" Deep
18" Wide X 7" Deep

Excalibur Series

Labels
ETL for US and
Canada for damp
location

ORDERING INFORMATION

Sample Number: EX-C-14-12W-AB-A

□	□	□	□	□	□	□
Series EX	Style Ceiling	Size 10" 14" 18"	LED 10" 8W 12W 14" 12W 24W 18" 24W 48W	Finish Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Textured Gold (TG) Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV) Polished Brass (PB) Adder Chrome (CH)	Lens White Acrylic (A) White Frosted (WF) White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS)	Options EMR, 700 Lumen EMR, 900 Lumen Dimming Drivers Design Modifications
	LED to CFL Lamp 8W = (1) F18DBX 12W = (2) F13DBX (1)F26DBX 24W = (2)F26DBX 48W = (4)F26DBX (2)F42TBX					