NEWPORT LED SERIES

Newport LED Wall Sconce features a Craftsman Style Cage Lantern, Luminous Three Panel Acrylic Diffuser, Decorative Strap Pattern, ADA Compliant

EVERGREEN LIGHTING

Catalog #		Type	
Project			
Comments		Date	
Prepared By			

SPECIFICATION FEATURES

Material
Paintlok Non Rust-able Steel construction spot welded for high quality appearance in a Three Panel Cage Design, standard powdercoat finish, white smooth acrylic flat panel lens, .125 thick, with open top and bottom.
Option: Wet Location with top and bottom lens or solid metal top cap.

Installation
Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Optics
Contact Evergreen Lighting for complete photometrics.

LED
Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage.
The LED arrays will be centered within the Lens area and mounted on a white aluminum reflective backplate.

Driver
Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:
- Constant Current
- 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67

Driver Options:
0-10V Dimming
Phase Dimming
Triac Dimming

10"H X 7"W X 4"D
13"H X 8"W X 4"D
16"H X 10"W X 5"D

Newport Series

Labels
ETL for US and Canada for damp or wet location

ORDERING INFORMATION

Sample Number: NE-W-13-24W-TR-A

Series	Style	Size	LED	Finish	Lens	Options

NE	Wall	10"
		13"
		16"
			10"
			  6W
			  12W
			13"
			  12W
			  24W
			16"
			  12W
			  24W
				Architectural Bronze (AB)
				Textured Bronze (TBR)
				Matte Black (MBK)
				Semi Gloss Black (GBK)
				Textured Black (TBK)
				Textured Rust (TR)
				Matte White (MW)
				Textured White (TW)
				Gloss White (GW)
				Metallic Grey (MG)
				Textured Gold (TG)
				Metallic Nickel (MN)
				Textured Verde Patina (TVP)
				Satin Brass (SB)
				Copper Vein (CV)
				Gold Vein (GV)
				Silver Vein (SV)
				Polished Brass (PB) Adder
				Chrome (CH)
					White Acrylic (A)
					White Frosted (WF)
					White Alabaster (WA)
					Honey Onyx (HO)
					Natural Horn (NH)
					Beige Alabaster (BA)
					Honey Swirl (HS)
						EMR, 700 Lumen
						EMR, 900 Lumen
						Dimming Drivers
						Design Modifications
						Larger size in ADA
						Wet Location
						  (Top and Bottom Lens)
						  (Solid Metal Top Cap)

LED to CFL Lamp
6W = (1) F13DBX
12W = (2) F13DBX
         (1)F26DBX
         (1)F27BX
24W = (2)F26DBX
         (2)F27BX

Evergreen Lighting
www.evergreenlighting.com