

PARKWOOD LED SERIES

Parkwood LED Wall Sconce features a Luminous Diffuser in Acrylic, Sheet Metal Construction with a clean Quartersphere Design, ADA Compliant

Catalog #		Type
Project		
Comments		Date
Prepared By		

EVERGREEN LIGHTING

SPECIFICATION FEATURES

Material

Paintlok Non Rustable Steel construction backplate Quartersphere Shaped Design, backplate white powdercoat finish, white smooth acrylic quartersphere shaped lens, .125 thick, with open top.

Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Optics

Contact Evergreen Lighting for complete photometrics.

LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage. The LED arrays will be centered within the Lens area and mounted on a white aluminum reflective backplate.

Driver

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67

Driver Options:
0-10V Dimming
Phase Dimming
Triac Dimming



6"H X 12"W X 4"D
8"H X 14"W X 4"D

Parkwood Series

Labels
ETL for US and
Canada for damp
location

ORDERING INFORMATION

Sample Number: PA-W-14-24W-GW-A

