

**VANCOUVER LED SERIES**

Vancouver LED Wall Sconce features a Square Solid Metal Housing Front with Decorative Round Hole Design for Up/Down Light, ADA Compliant

Catalog #		Type
Project		
Comments		Date
Prepared By		

**EVERGREEN LIGHTING**

**SPECIFICATION FEATURES**

**Material**

Paintlok Non Rustable Steel construction spot welded for high quality appearance in a Square Shaped Design, standard powdercoat finish, with a thin white acrylic inlay, with open top and bottom.

Option: Wet Location with top and bottom lens or a solid metal cap.

**Installation**

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

**Optics**

Contact Evergreen Lighting for complete photometrics.

**LED**


Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage. The LED arrays will be centered within the Lens area and mounted on a white aluminum reflective backplate.

**Driver**

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67

Driver Options:  
0-10V Dimming  
Phase Dimming  
Triac Dimming



9"H X 9"W X 4"D  
12"H X 12"W X 4"D

**Vancouver Series**

Labels  
ETL for US and  
Canada for damp or  
wet location

**ORDERING INFORMATION**

Sample Number: VA-W-12-24W-MN

<b>Series</b> VA	<b>Style</b> Wall	<b>Size</b> 9" 12"	<b>LED</b> 9" 6W 12W 12" 12W 24W	<b>Finish</b> Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Textured Gold (TG) Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV) Polished Brass (PB) Adder Chrome (CH)	<b>Lens</b> White Acrylic (A) White Frosted (WF) White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS)	<b>Options</b> EMR, 700 Lumen EMR, 900 Lumen Dimming Drivers Design Modifications Larger size in ADA Wet Location (Top and Bottom Lens) (Top metal cap)
	<b>LED to CFL Lamp</b> 6W = (1) F13DBX 12W = (2) F13DBX (1)F26DBX (1)F27BX 24W = (2)F26DBX (2)F27BX					