

CATHEDRAL HILL LED SERIES

Cathedral Hill LED Wall Sconce features a Luminous Diffuser in Acrylic, Sheet Metal Construction with Modern Decorative V Shaped Design, ADA Compliant

Catalog #		Type
Project		
Comments		Date
Prepared By		

SPECIFICATION FEATURES

Material

Paintlok Non Rustable Steel construction spot welded for high quality appearance in a sleek V Shaped Design, standard powdercoat finish, white smooth acrylic formed V shaped lens, .125 thick, with open top and bottom.

Option: Wet Location with top and bottom lens or solid metal top cap.

Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Optics

Contact Evergreen Lighting for complete photometrics.

LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage.

The LED arrays will be centered within the Lens area and mounted on a white aluminum reflective backplate.

Driver

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67

Driver Options:
0-10V Dimming
Phase Dimming
Triac Dimming










11"H X 7"W X 4"D
13"H X 7 1/2"W X 4"D
18"H X 11"W X 5"D

Cathedral Hill Series

Labels
ETL for US and
Canada for damp or
wet location

ORDERING INFORMATION

Sample Number: CH-W-13-12W-TR-A

						
Series CH	Style Wall	Size 11" 13" 18"	LED 11" 6W 12W 13" 12W 24W 18" 12W 24W	Finish Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Textured Gold (TG) Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV) Polished Brass (PB) Adder Chrome (CH)	Lens White Acrylic (A) White Frosted (WF) White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS)	Options EMR, 700 Lumen EMR, 900 Lumen Dimming Drivers Design Modifications Larger size in ADA Wet Location (Top and Bottom Lens) (Solid Metal Top Cap)
	LED to CFL Lamp 6W = (1) F13DBX 12W = (2) F13DBX (1)F26DBX 24W = (2)F26DBX					