

DESCRIPTION

Evolution 22 Series Exterior Wall Sconce features a Vacuum Formed Premium Quality White Acrylic diffuser, Aluminum 3 Flat Bar Fin Design Trim on the top and bottom, ADA Compliant, introducing LED Technology.

Catalog #		Type
Project		
Comments		Date
Prepared By		

EVERGREEN LIGHTING LED

SPECIFICATION FEATURES

Material

Aluminum 3 Flat Bar Fin Design Trim on the top and bottom combined with 16 gage aluminum sheet backpan with mounting fireplate, standard powdercoat finish baked at 400 degrees, Premium Quality 100% virgin white acrylic vacuum formed half cylinder lens with high impact DR additive, .125 thick, with formed top and bottom lens with no seams.

Installation

Supplied with 1/4" thick black neoprene gasket sealing the fixture to the wall. Also supplied with standard mounting hardware to mount to a 4" J-box.

Power Supply

Integral LED Power Supply for 120/277 volt, High Power Factor, AC/DC to 12 volt, constant voltage, constant current, Class 2, -40 degree C starting temperature, cold weather start

Optics

Contact Evergreen Lighting for complete photometrics.

LED

- 22":**
LED Board
(1)6W- 900 Lumen
(2)6W - 1800 Lumen
(1)15W- 2250 Lumen
(2)15W - 4500 Lumen
- 27":**
LED Board
(1) 15 watt - 2250 Lumen
(1) 24 watt - 3600 Lumen
(2) 15 watt - 4500 Lumen
(2) 24 watt - 7200 Lumen
- 32":**
LED Board
(2) 6 watt - 1800 Lumen
(4) 6 watt - 3600 Lumen
(2) 15 watt - 4500 Lumen
(4) 15 watt - 9000 Lumen
- 44":**
LED Board
(3) 6 watt - 2700 Lumen
(3) 15 watt - 6750 Lumen
(9) 15 watt - 13,500 Lumen



- 22"H X 8 1/2"W X 4"D
- 27"H X 9"W X 5"D
- 32"H X 9"W X 5"D
- 44"H X 9"W X 5"D

Evolution 22 Series LED

Labels
ETL for US and
Canada for Wet
Location

ORDERING INFORMATION

Sample Number: EVOL22-W-27-224LED-BA-WDA

EVOL22						
Series EVOL22	Style Wall	Size 22" 27" 32" 44"	Lamp 22" (1)6W LED (2)6W LED (1)15W LED (2)15W LED 27" (1)15W LED (1)24W LED (2)15W LED (2)24W LED 32" (2)6W LED (4)6W LED (2)15W LED (4)15W LED 44" (3)6W LED (3)15W LED (6)15W LED	Finish Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Textured Gold (TG) Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV) Brushed Aluminum (BA) Adder Polished Brass (PB) Adder	Acrylic Lens White Acrylic (WDA) Clear Frosted (CF) White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA)	Options EMR, 650 Lumen EMR, 900 Lumen Mark X Dimming Ballast Design Modifications Larger size in ADA Wet Location is Standard