

STOCKHOLM LED SERIES

Stockholm LED Wall Sconce features a Luminous Diffuser in Acrylic, Commercial Milled Round Bar Design with Perforated Front Accent, ADA Compliant

Catalog #		Type
Project		
Comments		Date
Prepared By		

EVERGREEN LIGHTING

SPECIFICATION FEATURES

Material

Aluminum Round Bar construction milled for high quality appearance, with a Perforated Top and Bottom Accent Band, standard powdercoat finish, P95 white frosted acrylic half cylinder lens, .125 thick, top and bottom lens or solid metal top.

Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Optics

Evergreen Lighting Website for complete photometrics.

LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage. The LED arrays will be centered within the Lens area and mounted on a decorative white aluminum reflective plate.

Driver

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 3 or 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67










15"H X 7"W X 4"D
 19"H X 9"W X 5 1/2"D
 24"H X 10"W X 5 1/2"D

Stockholm Series

DELIVERED LUMENS PER WATT
 2700K = 80
 3000K = 90
 3500K = 100
 4100K = 110
 5000K = 120

ORDERING INFORMATION

Sample Number: STO-W-24W-CH-WF

						
Series STO	Style Wall	Size 15" 19" 24"	LED 15" 12W 18W 24W 19" 12W 24W 30W 24" 20W 40W	Finish Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Brushed Aluminum (BA) adder Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV) Chrome (CH)	Lens White Frosted (WF) White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS)	Options EMR, 650 Lumen EMR, 900 Lumen Dimming Drivers Design Modifications Larger size in ADA

Labels
 ETL for US and
 Canada for WET
 location