

**TOSCANA LED SERIES**

Toscana LED Exterior Wedge Shaped Wall Sconce, DarkSky, features a Sleek Design with Luminous Bottom Lens, great application for shopping centers, cities, and multi family housing projects

DARK SKY

**EVERGREEN LIGHTING**

Catalog #		Type
Project		
Comments		Date
Prepared By		

**SPECIFICATION FEATURES**

**Material**

Paintlok Non-Rustable Steel construction for high quality appearance in a Wedge Shaped Cutoff Design, standard powder-coat finish, clear frosted acrylic flat panel lens, .125 thick

**Installation**

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

**Optics**

Contact Evergreen Lighting for complete photometrics.

**LED**

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage. The LED arrays will be centered within the Lens area and mounted on a white aluminum reflective backplate.

**Driver**

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67

Driver Options:  
0-10V Dimming  
Phase Dimming  
Triac Dimming



8"H X 7"W X 7"D  
12"H X 10"W X 12"D

**Toscana Series**

Labels  
ETL for US and  
Canada for wet  
location

**ORDERING INFORMATION**

Sample Number: TO-W-12-24W-AB-CFA

□	□	□	□	□	□	□
Series TO	Style Wall	Size 8" 12"	LED 8" 6W 12W 12" 12W 24W 36W	Finish Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Textured Gold (TG) Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV) Polished Brass (PB) Adder Chrome (CH)	Lens White Acrylic (A) Clear Frosted Acrylic (CFA) White Frosted (WF) White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS) Clear Frosted Glass (CFG)	Options EMR, 700 Lumen EMR, 900 Lumen Dimming Drivers Design Modifications
	<b>LED to CFL Lamp</b> 6W = (1) F13DBX 12W = (2) F13DBX (1) F26DBX 24W = (2) F26DBX (2) F32TBX 36W = (1) 70 MH = (1) 100 MH					