

DESCRIPTION

Evolution 20 Series Exterior Wall Sconce features a Vacuum Formed Premium Quality White Acrylic diffuser, Aluminum Flat Bar Fin Design Trim, ADA Compliant

Catalog #		Type
Project		
Comments		Date
Prepared By		

EVERGREEN LIGHTING LED

SPECIFICATION FEATURES

Material

Aluminum Flat Bar Trim construction combined with 16 gage aluminum sheet backpan with mounting fireplate, standard powdercoat finish baked at 400 degrees, Premium Quality 100% virgin white acrylic vacuum formed half cylinder lens with high impact DR additive, .125 thick, with formed top and bottom lens with no seams.

Installation

Supplied with 1/4" thick black neoprene gasket sealing the fixture to the wall. Also supplied with standard mounting hardware to mount to a 4" J-box.

Power Supply

Integral LED Power Supply for 120/277 volt, High Power Factor, AC/DC to 12 volt, constant voltage, constant current, Class 2, -40 degree C starting temperature, cold weather start

Optics

Contact Evergreen Lighting for complete photometrics.

LED

22":

LED Board
 (1)6W- 900 Lumen
 (2)6W - 1800 Lumen
 (1)15W- 2250 Lumen
 (2)15W - 4500 Lumen

27":

LED Board
 (1) 15 watt - 2250 Lumen
 (1) 24 watt - 3600 Lumen
 (2) 15 watt - 4500 Lumen
 (2) 24 watt - 7200 Lumen

32":

LED Board
 (2) 6 watt - 1800 Lumen
 (4) 6 watt - 3600 Lumen
 (2) 15 watt - 4500 Lumen
 (4) 15 watt - 9000 Lumen

44":

LED Board
 (3) 6 watt - 2700 Lumen
 (3) 15 watt - 6750 Lumen
 (9) 15 watt - 13,500 Lumen



22"H X 8 1/2"W X 4"D
 27"H X 9"W X 5"D
 32"H X 9"W X 5"D
 44"H X 9"W X 5"D

Evolution 20 Series LED

Labels
 ETL for US and
 Canada for Wet
 Location

EVOL20-W-22-12W-MBK-WDA-30K

Evolution 20 Series LED Fixture,
 12 watts of LED power, 3000K chip color,
 power supply for 277 volt,
 aluminum plate construction with matte black powdercoat finish,
 white acrylic formed lens, with fireplate,
 22"H X 8 1/2"W X 4"D,
 wet location