

Apollo LED Semi Flush

Apollo LED Semi Flush Series features a low profile bowl and is available in two diameters.

Catalog #		Type
Project		LED Semi Flush
Comments		
Prepared By		Date

EVERGREEN LIGHTING

SPECIFICATION FEATURES

Material

Aluminum round tube construction with an aluminum spun canopy for standard powdercoat finish or polished brass plated finish with a frosted white acrylic bowl. Single stem design with a 45 degree swivel mount.

Maximum overall hang height for one piece stem assembly is 5' (OA). Lengths from 5' to 25' must have a 5/8" deco connector that will be provided. Any lengths over 25' please contact Factory.

Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Optics

Contact Evergreen Lighting for complete photometrics.

LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum or FR4 PCB Board configured to the proper wattage. The LED arrays will be centered within the Lens area and mounted on a decorative white aluminum reflective plate.

Driver

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 3 or 5 year warranty
- 120/277 multivoltage on higher wattages
- IP66, IP67



16" diameter X 7"H on bowl
X 14" overall height

23" diameter X 10"H on bowl
X 16" overall height

DELIVERED LUMENS PER WATT

- 2700K = 80
- 3000K = 90
- 3500K = 100
- 4100K = 110
- 5000K = 120

ORDERING INFORMATION

Sample Number: APO-S-23-54W-GV-HO

Series APO	Style Semi Flush	Size 16" 23"	Lamp 16" 12W 18W 27W 23" 24W 36W	Finish Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Brushed Aluminum (BA) adder Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV) Chrome (CH)	Standard Lens White Frosted (WF) Optional Lens White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS)	Options LED EMR - Up to 24W (Iota ILB-3020) Dimming Drivers Stem Rod Length Swivel Canopy 16" Dust Cover 23" Dust Cover
				Labels ETL for US and Canada for indoor and damp location.		