

ARGENT BOLLARD SERIES

Catalog #	Туре
Project	LED
Comments	BOLLARD
Prepared By	Date

40°

DIMENSIONS: 40"H X 6"W

SPECIFICATIONS

Material

All parts are durable Aluminum Square Solid Bar with .063 solid aluminum sheet fabricated for maximum strength.

Lens

Standard White Frosted Premium Acrylic or Clear Frosted Premium Acrylic

LED

ALTA Long Life, high-efficiency, surface mount LEDs mounted on MPCB Aluminum Boards

Lifespan:

100,000 hour LED lifespan based on IES LM-80 results and TM-21 calculations

Driver

0-10V Dimming Driver for 120/277 volt, Constant Current, metal case, 5 year warranty

Label

ETL Listed for US and Canada for


ORDERING INFORMATION Sample Number: ARG-B-40-22W-AB-WF Finish Options Series Standard Lens Style Size ARG Bollard 32" Architectural Bronze (AB) White Frosted (WF) LED EMR - Up to 24W 40" Textured Bronze (TBR) Clear Frosted (CFA) OCC Sensors 12W Matte Black (MBK) Photo Cell Control 20W Semi Gloss Black (GBK) **Optional Lens** White Alabaster (WA) Textured Black (TBK) Textured Rust (TR) Honey Onyx (HO) 12W Matte White (MW) Natural Horn (NH) DELIVERED LUMENS PER WATT 20W Beige Alabaster (BA) Textured White (TW) 2700K = 80Honey Swirl (HS) Gloss White (GW) 3000K = 90Metallic Grey (MG) 3500K = 100Brushed Aluminum (BA) adder 4100K = 110Metallic Nickel (MN) 5000K = 120Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) **Evergreen Lighting** Silver Vein (SV) www.evergreenlighting.com Chrome (CH)



ARGENT BOLLARD SERIES

Instruction Sheet

Mounting Template



Mounting

Standard anchor bolts are 3/8" X 12" X 3". Bolts, nuts, and washers shall be hot dipped galvanized steel.

Warranty: Evergreen Lighting warrants Bollard LED products sold by Evergreen Lighting to be free from defects in material and workmanship for a period of One year for metal parts, a period of five 5 years for exterior housing powdercoat finish, a period of five 5 years for LED Light Engines and, a period of five 5 years for LED power components (driver), from the date of sale of such goods to the buyer as specified in Evergreen Lighting shipment documents for each product.




ARGENT BOLLARD SERIES

Photometrics

ARG-B-12W


ARG-B-20W

LUMINARE CLASSIFICATION SYSTEM (LOS) GRAPH



Luminaire Lumena: Front Low=130.5, Medium=400.0, Migh=110.4, Very High=2.2 Back: Low=144.0, Medium=399.5, High=112.9, Very High=2.1 Uplight: Low=0.7, High=3.5

BUG Rating : 81-U1-G0



Luminaire Lumens: Front Low=232.5, Medium=668.0, High=197.4, Very High=3.6 Back: Low=241.4, Medium=665.8, High=188.2, Very High=3.4 Uplight: Low=1.2, High=5.8

BUG Rating: B1-U1-G0



