ASPEN LED SERIES

Aspen LED Wall Sconce features a Cutoff V Shaped Solid Metal Housing Front Decorative Design for Up/Down Light, ADA Compliant

Catalog #	Туре
Project	
Comments	Date
Prepared By	

EVERGREEN LIGHTING

SPECIFICATION FEATURES

Material

Paintlok Non Rustable Steel construction spot welded for high quality appearance in a Cut-off V Shaped Design, standard powdercoat finish, with open top and bottom.

Option: Wet Location with top and bottom lens or a solid metal cap.

Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Optics

Contact Evergreen Lighting for complete photometrics.

LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage.

The LED arrays will be centered within the Lens area and mounted on a white aluminum reflective backplate.

Driver

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67

Driver Options: 0-10V Dimming Phase Dimming Triac Dimming




9"H X 12"W X 4"D 11"H X 14"W X 5"D

Aspen Series


Labels ETL for US and Canada for damp or wet location

ORDERING INFORMATION



24W = (2)F26DBX

Evergreen Lighting www.evergreenlighting.com



Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Textured Gold (TG) Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV) Polished Brass (PB) Adder Chrome (CH)

Lens
White Acrylic (A)
White Frosted (WF)
White Alabaster (WA)
Honey Onyx (HO)
Natural Horn (NH)
Beige Alabaster (BA)
Honey Swirl (HS)

Options
EMR, 700 Lumen
EMR, 900 Lumen
Dimming Drivers
Design Modifications
Larger size in ADA
Wet Location
(Top and Bottom Lens)
(Top metal cap)