Atlantis LED Semi Flush

Atlantis LED Semi Flush Series features a low profile bowl and is available in two diameters.

Catalog #		Туре
Project		LED Semi Flush
Comments		
Prepared By		Date

EVERGREEN LIGHTING

SPECIFICATION FEATURES

Material

Aluminum round spun trim construction with an aluminum spun canopy for standard powdercoat finish or polished brass plated finish with a frosted white acrylic bowl. Single stem design with a 45 degree swivel mount.

Maximum overall hang height for one piece stem assembly is 5' (OA). Lengths from 5' to 25' must have a 5/8" deco connector that will be provided. Any lengths over 25' please contact Factory.

Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Optics

Contact Evergreen Lighting for complete photometrics.

LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage.

The LED arrays will be centered within the Lens area and mounted on a decorative white aluminum reflective plate.

Driver

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 3 or 5 year warranty
- 120/277 multi voltage
- IP66, IP67



18" diameter X 9"H on bowl X 14" overall height

25" diameter X 12"H on bowl X 17" overall height

DELIVERED LUMENS PER WATT

2700K = 803000K = 90


3500K = 100

4100K = 110


5000K = 120

ORDERING INFORMATION

Sample Number: ATL-S-25-54W-GV-HO



Evergreen Lighting www.evergreenlighting.com



Finish

Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Brushed Aluminum (BA) adder Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV) Chrome (CH)

Standard Lens
White Frosted (WF)

Optional Lens White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS) Options LED EMR - Up to 24W (lota ILB-3020)

(lota ILB-3020) Dimming Drivers Stem Rod Length Swivel Canopy 18" Dust Cover 25" Dust Cover

Labels ETL for US and Canada for indoor and damp location.