

The Aurora Series

EVERGREEN LIGHTING CORPORATION



Left: Aurora Bollard, Size 20. Right: Size 30.

**ETL & CSA LISTED FOR WET LOCATIONS.
FACTORY TESTED BEFORE SHIPMENT.**

SIZES – Size 10 is the same style as the photo above left, except that it does not require the pedestal box. It is for LED, and fluorescent sources. Size 20, shown above left, is for LED, HID sources, and has the pedestal box. Size 30, shown above right, is for LED, fluorescent and HID sources, and always has the pedestal box. Please see the Size table.

HOUSING – Heavy duty cast aluminum.

OPTICS – Specular aluminum pathway lighting.

LENS – The standard lens is 1/8" thick clear tempered glass.

SOCKET – All sockets except fluorescent are glazed porcelain, medium base, rated to 600V.

ELECTRICAL COMPONENTS – Available in MH, LED

All HID ballasts are CWA/HPF regulating auto-transformers. Starting temperature is -40°F for LED and MH starts at -20°F. Maximum wattage is 100W for MH. Options: Maximum wattage for PL fluorescent is 42W. Maximum wattage for incandescent is 100W. Fluorescent is available in 120V or 277V only.

ANCHOR BASE AND BOLTS – Four (4) 3/8" by 12" galvanized anchor bolts are supplied, complete with two each nuts and washers. The anchor base plate is made of heavy-duty aluminum.

FINISH – The finish is thermoset polyester oven-baked powder coat, in any standard Evergreen color. Custom colors are available to your specifications; consult factory.

EVERGREEN LIGHTING MANUFACTURERS OF QUALITY LIGHTING EQUIPMENT

1379 RIDGEWAY STREET, POMONA, CA 91768

voice: **909-865-5599** fax: **909-865-5539**

email: sales@evergreenlighting.com visit us online at: www.evergreenlighting.com



The Aurora Series

	1	2	3	4	5	6	7
FIXTURE	SIZE	SOURCE	VOLTS	LAMP	LENS	COLOR	OPTIONS
AUR	30	L10	2	L	1	GR	MT, QR

Create a catalog number from the tables below. Example number: AUR – 30 – L10 – 2– L – 1 – GR – MT, QR

1 SIZE


	A	B	C	D	E
Size = 10	40"	9-1/2"	7"	12"	9"
Size = 20	40"	9-1/2"	7"	12"	9"
Size = 30	40"	9-1/2"	7"	12"	9"


ALL SIZES MAX WATTS:

36W LED
100W MH
42W CFL


NOTE ON DIMENSIONS:

A IS THE OVERALL HEIGHT
B IS THE BASE SIDE-TO-SIDE
C IS THE BASE FRONT-TO-BACK
D IS THE SHAFT AND HEAD FRONT-TO-BACK
E IS THE SHAFT AND HEAD SIDE-TO-SIDE







Size 10
fluorescent and
incandescent.



Size 20
HPS and MH



Size 30
fluorescent,
incandescent,
HPS and MH



front view

2 LIGHT SOURCE

	LED	MH
10W	L10	
20W	L20	
36W	L36	
70W		E2
100W		H2

FLUORESCENT

X = single PL
Y = dual PL
(specify wattage up to 42W single PL or 13W dual PL)

Z = incandescent
(Please specify type and wattage up to 100W, medium base only.)

3 VOLTAGE

120V = 2 *Also available in Multi-Tap; see Options table*

208V = 0

240V = 4

277V = 7

4 LAMP

L = with lamp
N = no lamp

NOTE: EVERGREEN DOES NOT FURNISH INCANDESCENT LAMPS

5 LENS

1 = clear tempered glass.
2 = custom; *please consult factory*

480V = 8 *Not available in Multi-Tap*

NOTE: FLUORESCENT SOURCES AVAILABLE IN 120V OR 277V ONLY.

6 COLOR

BK = Black	BU = Blue
GR = Green	SL = Silver
WH = White	GY = Gray
DB = Dark Bronze	CC = Custom Color
VP = Verde Patina	

7 OPTIONS

MT = multi-tap transformer
QR = quartz restrike
FV = international ballast; specify cycles

EVERGREEN LIGHTING CORPORATION