

BOSTON LED WALL VANITY SERIES

Boston LED Wall Vanity Fixture features a Linear C-Shaped Design with a Center Band, White Acrylic Lens, and displays a clean glow

Catalog #		Type
Project		
Comments		Date
Prepared By		

EVERGREEN LIGHTING

SPECIFICATION FEATURES

Material

Paintlok Non-Rustable Steel construction spot welded for high quality appearance, standard powdercoat finish, white smooth acrylic lens, 1/8" thick.

Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Optics

Contact Evergreen Lighting for complete photometrics.

LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage. The LED arrays will be centered within the Lens area and mounted on a white aluminum reflective backplate.

Driver

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67



6"H X 20"W X 5"D

Boston Series

Labels
ETL for US and
Canada for damp
location

ORDERING INFORMATION

Sample Number: BO-W-20-12W-TBR-A

□	□	□	□	□	□	□
Series BO	Style Wall	Size 20"	LED 20" 12W 24W 36W	Finish Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Textured Gold (TG) Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV) Polished Brass (PB) Adder Chrome (CH)	Lens White Acrylic (A) White Frosted (WF) White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS)	Options EMR, 700 Lumen EMR, 900 Lumen Dimming Drivers Design Modifications
	LED to CFL Lamp 12W = (2) F13DBX 24W = (2) F26DBX 36W = (2) F32TBX (2) F42TBX					