Broadway LED Ceiling Flush

Broadway LED Ceiling Flush Series features a low profile circular deco shape and is available in two diameters.

Catalog #	Туре
Project	LED Ceiling
Comments	Flush
Prepared By	Date

EVERGREEN LIGHTING

SPECIFICATION FEATURES

Material

Aluminum solid flat bar construction with an aluminum spun canopy for standard powdercoat finish or polished brass plated finish with P95 frosted white acrylic formed lens.

Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Optics

Contact Evergreen Lighting for complete photometrics.

LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage.

The LED arrays will be centered within the Lens area and mounted on a decorative white aluminum reflective plate.

Driver

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 3 or 5 year warranty
- 120/277 volt multi-voltage power supplies
- IP66, IP67



18" diameter X 7"H on fixture

24" diameter X 7"H on fixture


DELIVERED LUMENS PER WATT

2700K = 80 3000K = 90 3500K = 1004100K = 110


5000K = 120

ORDERING INFORMATION

Sample Number: BWY-C-24-54W-TBK-WF



Evergreen Lighting www.evergreenlighting.com



Finish

Chrome (CH)

Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Brushed Aluminum (BA) adder Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV)

Standard Lens
White Frosted (WF)

Optional Lens White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS)

> Labels ETL for US and Canada for indoor and damp location.

Options

Dimming Drivers

LED EMR - Up to 24W

(lota ILB-3020)