Broadway LED Semi Flush

Broadway LED Semi Flush Series features a low profile circular deco shape and is available in two diameters.

C	Catalog #	Туре
	Project	LED Semi Flush
	Comments	Tush
	Prepared By	Date

EVERGREEN LIGHTING

SPECIFICATION FEATURES

Material

Aluminum solid flat bar construction with an aluminum spun canopy for standard powdercoat finish or polished brass plated finish with P95 frosted white acrylic formed lens. Four rod design with a separate canopy assembly for 45 degree swivel mount (option).

Maximum overall hang height for one piece stem assembly is 5' (OA). Lengths from 5' to 25' must have a 5/8" deco connector that will be provided. Any lengths over 25'contact Factory. **Installation**

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Optics

Contact Evergreen Lighting for complete photometrics.

LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage.

The LED arrays will be centered within the Lens area and mounted on a decorative white aluminum reflective plate.

Driver

Specific Drivers will be matched with each different LED array configuration/ wattage. Standard Driver features are:

- Constant Current
- 3 or 5 year warranty
- 120/277 volt multi-voltage power supplies
- IP66, IP67



18" diameter X 7"H on bowl X 14" overall height

24" diameter X 7"H on bowl X 14" overall height

DELIVERED LUMENS PER WATT

2700K = 80 3000K = 90 3500K = 100 4100K = 110 5000K = 120

