

DENALI LED SERIES

Denali LED Wall Sconce features a Luminous Diffuser in Acrylic, Commercial Milled Square Bar Design, ADA Compliant

Catalog #		Type
Project		
Comments		Date
Prepared By		

EVERGREEN LIGHTING

SPECIFICATION FEATURES

Material

Aluminum Square Bar construction milled for high quality appearance, standard powdercoat finish, P95 white smooth acrylic half cylinder lens, .125 thick, with open top and bottom. Option: Wet Location with top and bottom lens, or with solid metal top cap.

Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Optics

Contact Evergreen Lighting for complete photometrics.


LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage. The LED arrays will be centered within the Lens area and mounted on a white aluminum reflective backplate.

Driver

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67



10"H X 6"W X 4"D
 15"H X 9"W X 4"D
 20"H X 10"W X 5 1/2"D

Denali Series

Labels
 ETL for US and
 Canada for damp or
 wet location

ORDERING INFORMATION

Sample Number: DE-W-15-18W-CH-WF

Series DE	Style Wall	Size 10" 15" 20"	LED 10" 8W 12W 16W 15" 12W 18W 24W 20" 12W 24W 30W	Finish Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Textured Gold (TG) Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV) Polished Brass (PB) Adder Chrome (CH)	Lens White Frosted (WF) White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS)	Options EMR, 700 Lumen EMR, 900 Lumen Dimming Drivers Design Modifications Larger size in ADA Wet Location (Top and Bottom Lens) (Solid Metal Top)
		LED to CFL Lamp 8W = (1) F18DBX 12W = (2) F13DBX 16W = (2) F18DBX 12W = (2) F13DBX 18W = (2) F18DBX 24W = (2) F26DBX 12W = (1) F27BX 24W = (2) F27BX 30W = (2) F32TBX				