

EMBARCADERO LED CEILING SERIES

Embarcadero LED Flush Round Ceiling Fixture features a Modern Double Square Bar Trim Ring with a drop acrylic bowl.

Catalog #		Type
Project		
Comments		Date
Prepared By		

EVERGREEN LIGHTING

SPECIFICATION FEATURES

Material

Aluminum Square Bar construction milled for high quality appearance, standard powdercoat finish, P95 white smooth acrylic bowl lens, .125 thick.

Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Optics

Contact Evergreen Lighting for complete photometrics.

LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage.

The LED arrays will be centered within the Lens area and mounted on a white aluminum reflective backplate.

Driver

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67



15" Diameter X 6" Deep
19" Diameter X 7" Deep

Embarcadero Series

Labels
ETL for US and
Canada for damp
location

ORDERING INFORMATION

Sample Number: EM-C-15-12W-MN-A

□	□	□	□	□	□	□
Series	Style	Size	LED	Finish	Lens	Options
EM	Ceiling	15" 19"	15" 8W 12W 24W 19" 24W 48W	Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Textured Gold (TG) Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV) Polished Brass (PB) Adder Chrome (CH)	White Acrylic (A) White Frosted (WF) White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS)	EMR, 700 Lumen EMR, 900 Lumen Dimming Drivers Design Modifications
	LED to CFL Lamp 8W = (1) F18DBX 12W = (2) F13DBX (1)F26DBX 24W = (2)F26DBX 48W = (4)F26DBX (2)F42TBX					