

Essex LED Ceiling Flush

Essex LED Ceiling Flush Series features a low profile bowl and is available in two diameters with a triple rod drop design.

Catalog #		Type
Project		LED Ceiling Flush
Comments		
Prepared By		Date

EVERGREEN LIGHTING

SPECIFICATION FEATURES

Material

Aluminum round tube construction with an aluminum spun canopy for standard powdercoat finish or polished brass plated finish with a frosted white acrylic bowl.

Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Optics

Contact Evergreen Lighting for complete photometrics.

LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage. The LED arrays will be centered within the Lens area and mounted on a decorative white aluminum reflective plate.

Driver

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 3 or 5 year warranty
- 120/277 multi voltage power supply
- IP66, IP67



16" diameter X 7"H on bowl

23" diameter X 10"H on bowl

DELIVERED LUMENS PER WATT

2700K = 80
3000K = 90
3500K = 100
4100K = 110
5000K = 120

ORDERING INFORMATION

Sample Number: ESX-C-23-54W-CH-WF

Series	Style	Size	Lamp	Finish	Standard Lens	Options
ESX	Ceiling Flush	16" 23"	16" 12W 18W 27W 23" 24W 36W	Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Brushed Aluminum (BA) adder Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV) Chrome (CH)	White Frosted (WF) Optional Lens White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS)	LED EMR - Up to 24W (Iota ILB-3020) Dimming Drivers

Evergreen Lighting
www.evergreenlighting.com

Labels
ETL for US and Canada for indoor and damp location.