

**GEORGETOWN LED SERIES**

Georgetown LED Wall Sconce features a Luminous Diffuser in Acrylic, Commercial Milled Flat Bar Design, ADA Compliant

Catalog #		Type
Project		
Comments		Date
Prepared By		

**EVERGREEN LIGHTING**

**SPECIFICATION FEATURES**

**Material**

Aluminum Flat Bar construction slotted and milled for high quality appearance, standard powder-coat finish, P95 white frosted acrylic half cylinder lens, .125 thick, with top and bottom lens or solid metal top.

**Installation**

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

**Optics**

Evergreen Lighting Website for complete photometrics.

**LED**

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage. The LED arrays will be centered within the Lens area and mounted on a decorative white aluminum reflective plate.

**Driver**

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 3 or 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67









15"H X 7"W X 4"D  
19"H X 9"W X 5 1/2"D  
24"H X 10"W X 5 1/2"D

**Georgetown Series**

DELIVERED LUMENS PER WATT  
2700K = 80  
3000K = 90  
3500K = 100  
4100K = 110  
5000K = 120

**ORDERING INFORMATION**

Sample Number: GEO-W-24W-CH-WF

						
<b>Series</b> GEO	<b>Style</b> Wall	<b>Size</b> 15" 19" 24"	<b>LED</b> 15" 12W 18W 24W 19" 12W 24W 30W 24" 20W 40W	<b>Finish</b> Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Brushed Aluminum (BA) adder Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV) Chrome (CH)	<b>Lens</b> White Frosted (WF) White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS)	<b>Options</b> EMR, 650 Lumen EMR, 900 Lumen Dimming Drivers Design Modifications Larger size in ADA

Labels  
ETL for US and  
Canada for WET  
location