Hamilton LED Ceiling Flush

Hamilton LED Ceiling Flush Series features a low profile bowl and is available in two diameters.

Catalog #		Туре
Project		LED Ceiling Flush
Comments		
Prepared By		Date

EVERGREEN LIGHTING

SPECIFICATION FEATURES

Material

Aluminum round spun trim construction for standard powdercoat finish or polished brass plated finish with a frosted white acrylic bowl.

Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Optics

plete photometrics.

LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper watt-

The LED arrays will be centered within the Lens area and mounted on a decorative white aluminum reflective plate.

Driver

Specific Drivers will be matched with each different LED array configuration/ Evergreen Lighting Website for com- wattage. Standard Driver features are:

- **Constant Current**
- 3 or 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67



18" diameter X 8"H on bowl

25" diameter X 11"H on bowl

DELIVERED LUMENS PER WATT

2700K = 80


3000K = 90

3500K = 100


4100K = 1105000K = 120

ORDERING INFORMATION

Sample Number: HAM-C-25-54W-SB-WF



Evergreen Lighting www.evergreenlighting.com



Finish

Silver Vein (SV)

Chrome (CH)

Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Brushed Aluminum (BA) adder Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV)

Standard Lens White Frosted (WF)

Optional Lens White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA)

Honey Swirl (HS)

LED EMR - Up to 24W (lota ILB-3020) Dimming Drivers

Options

Labels FTL for US and Canada for indoor and damp location.