

Hamilton LED Pendant

Hamilton LED Pendant Series features a low profile bowl and is available in two diameters.

Catalog #		Type
Project		LED Pendant
Comments		Date
Prepared By		

EVERGREEN LIGHTING

SPECIFICATION FEATURES

Material

Aluminum round spun trim construction with an aluminum spun canopy for standard powdercoat finish or polished brass plated finish with a frosted white acrylic bowl. Decorative 3 stem design with a decorative rod canopy kit (option) for 45 degree swivel mount.

Maximum overall hang height for one piece stem assembly is 3' (OA). Any lengths over 3' please contact factory.

Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Optics

Evergreen Lighting Website for complete photometrics.

LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage. The LED arrays will be centered within the Lens area and mounted on a decorative white aluminum reflective plate.

Driver

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 3 or 5 year warranty
- 120/277 Multi voltage
- IP66, IP67



30" diameter X12"H on bowl
X 36" overall height

37" diameter X 16"H on bowl
X 40" overall height

DELIVERED LUMENS PER WATT

- 2700K = 80
- 3000K = 90
- 3500K = 100
- 4100K = 110
- 5000K = 120

ORDERING INFORMATION

Sample Number: HAM-P-37-90W-TBR-WA

Series HAM	Style Pendant	Size 30" 37"	Lamp 30" 36W 54W 72W 37" 72W 90W	Finish Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Brushed Aluminum (BA) adder Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV) Chrome (CH)	Standard Lens White Frosted (WF) Optional Lens White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS)	Options LED EMR - Up to 24W (Iota ILB-3020) Dimming Drivers Stem Rod Length Swivel Canopy 30" Dust Cover 37" Dust Cover Multiple Rod Designs
				Labels ETL for US and Canada for indoor and damp location.		