MADISON LED SERIES

Madison LED Wall Sconce features a Luminous Diffuser in Acrylic, Sheet Metal Construction with a clean Trim Band and Strap Half Cylinder Design, ADA Compliant

	Catalog #	Туре
)	Project	
	Comments	Date
	Prepared By	

SPECIFICATION FEATURES

Material

Paintlok Non Rustable Steel construction spot welded for high quality appearance in a half cylinder Shaped Design, standard powdercoat finish, white smooth acrylic half cylinder shaped lens, .125 thick, with open top and bottom. Option: Wet Location with top and bottom lens or solid metal top cap.

Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Optics

Contact Evergreen Lighting for complete photometrics.

LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage.

The LED arrays will be centered within the Lens area and mounted on a white aluminum reflective backplate.

Driver

٠

Specific Drivers will be matched with each different LED array configuration/ wattage. Standard Driver features are:

- Constant Current
- 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67

Driver Options: 0-10V Dimming Phase Dimming Triac Dimming



10"H X 7 1/2"W X 4"D 12"H X 9"W X 4"D 16"H X 11"W X 5"D

Madison Series

Labels ETL for US and Canada for damp or wet location

