

## SANTA CLARA LED SERIES

Santa Clara LED Wall Sconce features a Craftsman Style Cage Lantern, Luminous Three Panel Acrylic Diffuser, Decorative Strap Pattern, ADA Compliant

Catalog #		Type
Project		
Comments		Date
Prepared By		

## EVERGREEN LIGHTING

### SPECIFICATION FEATURES

#### Material

Paintlok Non Rust-able Steel construction spot welded for high quality appearance in a Three Panel Cage Design, standard powdercoat finish, white smooth acrylic flat panel lens, .125 thick, with open top and bottom.

Option: Wet Location with top and bottom lens or solid metal top cap.

#### Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

#### Optics

Contact Evergreen Lighting for complete photometrics.

#### LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage.

The LED arrays will be centered within the Lens area and mounted on a white aluminum reflective backplate.

#### Driver

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67

Driver Options:  
0-10V Dimming  
Phase Dimming  
Triac Dimming



10"H X 7"W X 4"D  
13"H X 8"W X 4"D  
16"H X 10"W X 5"D

### Santa Clara Series

Labels  
ETL for US and  
Canada for damp or  
wet location

### ORDERING INFORMATION

Sample Number: SC-W-13-24W-AB-A

Series	Style	Size	LED	Finish	Lens	Options
SC	Wall	10" 13" 16"	10" 6W 12W 13" 12W 24W 16" 12W 24W	Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Textured Gold (TG) Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV) Polished Brass (PB) Adder Chrome (CH)	White Acrylic (A) White Frosted (WF) White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS)	EMR, 700 Lumen EMR, 900 Lumen Dimming Drivers Design Modifications Larger size in ADA Wet Location (Top and Bottom Lens) (Solid Metal Top Cap)
<b>LED to CFL Lamp</b>						
6W = (1) F13DBX						
12W = (2) F13DBX						
(1)F26DBX						
(1)F27BX						
24W = (2)F26DBX						
(2)F27BX						

Evergreen Lighting  
www.evergreenlighting.com