

ST. PAUL LED SERIES

St. Paul LED Wall Sconce features a Luminous Bell Shaped Diffuser in Acrylic, Sheet Metal Construction with a decorative Top trim, bottom cap and finial, ADA Compliant

Catalog #		Type
Project		
Comments		Date
Prepared By		

EVERGREEN LIGHTING

SPECIFICATION FEATURES

Material

Paintlok Non Rustable Steel construction spot welded for high quality appearance in a Bell Shaped Design, standard powdercoat finish, white smooth bell shaped lens, .125 thick, with open top.

LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage. The LED arrays will be centered within the Lens area and mounted on a white aluminum reflective backplate.

Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Driver

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67

Optics

Contact Evergreen Lighting for complete photometrics.

Driver Options:
0-10V Dimming
Phase Dimming
Triac Dimming



10"H X 10"W X 4"D

St. Paul Series

Labels
ETL for US and
Canada for damp
location

ORDERING INFORMATION

Sample Number: SP-W-10-12W-SB-WF

□	□	□	□	□	□	□
Series	Style	Size	LED	Finish	Lens	Options
SP	Wall	10"	10" 6W 12W 24W	Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Textured Gold (TG) Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV) Polished Brass (PB) Adder Chrome (CH)	White Acrylic (A) White Frosted (WF) White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS)	Remote EMR, 700 Lumen Remote EMR, 900 Lumen Dimming Drivers
	LED to CFL Lamp 6W = (1) F13DBX 12W = (2) F13DBX (1)F26DBX 24W = (2)F26DBX					