Victoria LED Semi Flush

Victoria LED Semi Flush Series features a low profile bowl and is available in two diameters.

Catalog #	Туре
Project	LED Semi
Comments	Flush
Prepared By	Date

EVERGREEN LIGHTING

SPECIFICATION FEATURES

Material

Aluminum square solid bar construction with an aluminum spun canopy for standard powdercoat finish with a frosted white acrylic bowl. Four straight stem design with a round canopy mount. Maximum overall hang height for one piece stem assembly is 5' (OA). Lengths from 5' to 25' must have a 5/8" deco connector that will be provided. Any lengths over 25' please contact Factory.

Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Optics

Evergreen Lighting Website for complete photometrics.

LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper watt-

The LED arrays will be centered within the Lens area and mounted on a decorative white aluminum reflective plate.

Driver

Specific Drivers will be matched with each different LED array configuration/ wattage. Standard Driver features are:

- **Constant Current**
- 3 or 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67



16" diameter X 7"H on bowl X 14" overall height

23" diameter X 10"H on bowl X 16" overall height

DELIVERED LUMENS PER WATT

2700K = 803000K = 90


3500K = 100

4100K = 110


5000K = 120

ORDERING INFORMATION

Sample Number: VCT-S-23-54W-AB-HS



Evergreen Lighting www.evergreenlighting.com



Finish

Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Brushed Aluminum (BA) adder Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV) Chrome (CH)

Standard Lens White Frosted (WF)

White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS)

Optional Lens

Stem Rod Length **Swivel Canopy** 16" Dust Cover 23" Dust Cover

Options

Dimming Drivers

LED EMR - Up to 24W

(lota ILB-3020)

Labels ETL for US and Cana-

da for indoor and damp location.