#### Warwick LED Semi Flush

Warwick LED Semi Flush Series features a low profile bowl and is available in two diameters.

Catalog #		Туре
Project		LED Semi Flush
Comments		
Prepared By		Date

# **EVERGREEN LIGHTING**

#### SPECIFICATION FEATURES

## Material

Aluminum square solid bar construction with an aluminum spun canopy for standard powdercoat finish with a frosted white acrylic bowl. Four stem design with straight rods for canopy mount. Maximum overall hang height for one piece stem assembly is 5' (OA). Lengths from 5' to 25' must have a 5/8" deco connector that will be provided. Any lengths over 25' please contact Factory.

## Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

# **Optics**

Evergreen Lighting Website for complete photometrics.

## LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage.

The LED arrays will be centered within the Lens area and mounted on a decorative white aluminum reflective plate.

#### Driver

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 3 or 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67



16" diameter X 7"H on bowl X 14" overall height

23" diameter X 10"H on bowl X 16" overall height

DELIVERED LUMENS PER WATT


2700K = 803000K = 90

3500K = 1004100K = 110


5000K = 120

## ORDERING INFORMATION





Evergreen Lighting www.evergreenlighting.com



#### Finish

Chrome (CH)

Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Brushed Aluminum (BA) adder Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV)

# Standard Lens White Frosted (WF)

Optional Lens White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS)

# Options

LED EMR - Up to 24W (lota ILB-3020) Dimming Drivers Stem Rod Length Swivel Canopy 16" Dust Cover 23" Dust Cover

Labels

ETL for US and Canada for indoor and damp location.