

WILMINGTON LED WALL VANITY SERIES

Wilmington LED Wall Vanity Fixture features a Linear Low Profile Scoop Shaped Solid Bar Design with Solid Metal End Caps, White Frosted Acrylic Lens, and displays a clean and modern look.

Catalog #		Type
Project		
Comments		Date
Prepared By		

EVERGREEN LIGHTING

SPECIFICATION FEATURES

Material

Aluminum Square Solid Bar construction with Two Bar Design on each side and in the middle, milled and screwed to backplate for high quality appearance, solid metal end caps, standard powdercoat finish, white frosted acrylic lens, 1/8" thick.

Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Optics

Contact Evergreen Lighting for complete photometrics.


LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper wattage. The LED arrays will be centered within the Lens area and mounted on a white aluminum reflective backplate.

Driver

Specific Drivers will be matched with each different LED array configuration/wattage. Standard Driver features are:

- Constant Current
- 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67



5"H X 24"W X 5"D
 5"H X 36"W X 5"D
 5"H X 48"W X 5"D

Wilmington Series

Labels
 ETL for US and
 Canada for damp
 location

ORDERING INFORMATION

Sample Number: WL-W-36-24W-TR-WF

Series WL	Style Wall	Size 24" 36" 48"	LED 24" 8W 16W 36" 12W 24W 48" 16W 32W	Finish Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Textured Gold (TG) Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV) Polished Brass (PB) Adder Chrome (CH)	Lens White Acrylic (A) White Frosted (WF) White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS)	Options EMR, 700 Lumen EMR, 900 Lumen Dimming Drivers Design Modifications
	LED to CFL Lamp 8W = (1) F17T8 12W = (1) F25T8 16W = (2) F17T8 = (1) F32T8 24W = (2) F25T8 32W = (2) F32T8					