Wilshire LED Ceiling Flush

Wilshire LED Ceiling Flush Series features a low profile bowl and is available in two diameters.

Catalog #	Туре
Project	LED
Comments	Ceiling Flush
Prepared By	Date

EVERGREEN LIGHTING

SPECIFICATION FEATURES

Material

Aluminum round spun trim construction for standard powdercoat finish or polished brass plated finish with a frosted white acrylic bowl.

Installation

Supplied with standard mounting hardware to mount to a 4" J-box or plaster ring

Optics

Evergreen Lighting Website for complete photometrics.

LED

Alta #AL-R-1W-30 LED array to be mounted onto an Aluminum MPCB Board configured to the proper watt-

The LED arrays will be centered within the Lens area and mounted on a decorative white aluminum reflective plate.

Driver

Specific Drivers will be matched with each different LED array configuration/ wattage. Standard Driver features are:

- **Constant Current**
- 3 or 5 year warranty
- 120/277 multi-voltage power supplies
- IP66, IP67



18" diameter X 8"H on bowl


25" diameter X 11"H on bowl

DELIVERED LUMENS PER WATT


2700K = 803000K = 903500K = 1004100K = 1105000K = 120

ORDERING INFORMATION

Sample Number: WIL-C-25-54W-SB-WF



Evergreen Lighting www.evergreenlighting.com



Finish

Architectural Bronze (AB) Textured Bronze (TBR) Matte Black (MBK) Semi Gloss Black (GBK) Textured Black (TBK) Textured Rust (TR) Matte White (MW) Textured White (TW) Gloss White (GW) Metallic Grey (MG) Brushed Aluminum (BA) adder Metallic Nickel (MN) Textured Verde Patina (TVP) Satin Brass (SB) Copper Vein (CV) Gold Vein (GV) Silver Vein (SV) Chrome (CH)

Standard Lens White Frosted (WF)

Optional Lens White Alabaster (WA) Honey Onyx (HO) Natural Horn (NH) Beige Alabaster (BA) Honey Swirl (HS)

> Labels ETL for US and Canada for indoor and

Options

Dimming Drivers

LED EMR - Up to 24W

(lota ILB-3020)

damp location.